



TECHNICAL DATA

PRO-GEAR 75W-90 FS

Fully synthetic gear oil

Product code: FP75FS

Product Description:

PRO-GEAR 75W-90 FS is a fully synthetic gear oil manufactured from very high quality synthetic base stocks, highly effective extreme pressure and anti-wear additives and premium shear stable viscosity modifiers.

PRO-GEAR 75W-90 FS offers unsurpassed load carrying capacity, which is essential for shock load, high torque and high speed service operation. The high thermal stability of the product's components allows extended oil drain intervals to be realised and the levels of protection provided ensure maximum component durability.

Benefits:

- Fully synthetic, long oil drain formulation
- Excellent low temperature fluidity
- Maximum component protection
- High levels of oxidation resistance
- Outstanding thermal stability

Applications:

PRO-GEAR 75W-90 FS is recommended for a variety of highly stressed manual gearboxes, heavily loaded axle drives, transfer boxes and other transmission equipment found in many passenger cars, light and heavy-duty commercial vehicles and off-highway applications.

Product Specification:

API	GL-4, GL-5
-----	------------

Typical Test Data:

Appearance	Clear & Bright
Density @ 20°C	0.868
Kinematic Viscosity @ 40°C (cSt)	105.8
Kinematic Viscosity @ 100°C (cSt)	15.5
Viscosity Index	155



TECHNICAL DATA

Brookfield Viscosity @ -40°C (cP)	138,000
Flash Point COC (°C)	220

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.