



TECHNICAL DATA

PRO-GEAR 75W-90 SS

Semi synthetic based GL-5 & GL-4 gear oil

Product code: FP75SS

Product Description:

PRO-GEAR 75W-90 SS is new generation of extreme pressure, semi-synthetic, multigrade gear oil meeting the API performance levels GL-4 and GL-5. PRO-GEAR 75W-90 SS gear oil is manufactured from high quality synthetic hydrocarbon base stocks which have a high viscosity index and a combination of mineral oils and extreme pressure (EP) additives to provide a lubricant with outstanding anti wear protection. It is designed to cope with high shock load, high torque and high-speed service conditions.

Benefits:

- Excellent oxidation stability
- Outstanding low and high temperature performance
- May be used where an SAE 80W-90, 85W-90 or 90, API GL-4 or GL-5 oil is specified
- Long service life
- Suitable for use in most synchromesh gearboxes and hypoid axle units
- Improved fuel economy

Applications:

PRO-GEAR 75W-90 SS is suitable for the majority of manual gearboxes, including hypoid gears, synchromesh gearboxes and final drives fitted to automotive and commercial vehicles.

Typical Test Data:

Density @ 15.6°C (g / ml)	0.876
Kinematic Viscosity @ 100°C (cSt)	15.94
Kinematic Viscosity @ 40°C (cSt)	95.02
Viscosity Index	179
Flash Point COC (°C)	225
Pour Point (°C)	-40

Product Specification:



TECHNICAL DATA

API	GL-4 & GL-5
-----	-------------

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.