



TECHNICAL DATA

PRO-GEAR 75W FS

Fully synthetic low viscosity manual transmission fluid

Product code: FP75W

Product Description:

PRO-GEAR 75W FS is a fully synthetic low-viscosity manual transmission fluid that can be used in a wide variety of modern vehicles. It is formulated using carefully selected synthetic basestocks and specialised advanced additives, designed to protect transmission systems and offer the best possible fuel economy in all driving conditions.

Benefits:

- Multi-vehicle fluid specified by many manufacturers
- Excellent fuel economy properties
- Outstanding performance across a wide temperature range
- Long-lasting formulation, designed for maximum product life

Application:

PRO-GEAR 75W FS is suitable for synchronised manual transmissions where a fluid of this type is specified by the vehicle manufacturer. It may also be used in some dry-clutch DCT systems where a fluid of this type is specified.

Product Specification:

API	GL-4
BMW	MTF LT-3
Ford	M2C200D-2, M2C200D-3
PSA	Special PSA fluid, part no. 1618078480 9730A8
VW	G 052 178, G 052 512, G 052 527 G 052 726, G 060 726, G 070 726

Typical Test Data:



TECHNICAL DATA

Density @ 20°C	0.840
Kinematic Viscosity @ 100°C (cSt)	6.5
Kinematic Viscosity @ 40°C (cSt)	33.5
Viscosity Index	151
Pour Point (°C)	-45

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.