



TECHNICAL DATA

PRO-GEAR 80W-90 LS

Mineral oil based gear oil for limited slip differentials

Product code: FP80LS

Product Description:

PRO-GEAR 80W-90 LS is a specially formulated extreme pressure gear oil for use in limited slip differentials.

PRO-GEAR 80W-90 LS is manufactured from high quality base oils, performance EP additives and specially selected friction modifiers to provide a lubricant meeting the exacting requirements of limited slip operations.

Benefits:

- Reduces whining and chattering
- Excellent high temperature stability
- Ensures clutches slide smoothly
- Extreme pressure properties

Application:

PRO-GEAR 80W-90 LS is suitable for limited slip differentials fitted to cars, vans, trucks, buses, and agricultural and construction equipment.

Product Specification:

API	GL-5 LS
-----	---------

Typical Test Data:

SAE Viscosity	80W-90
Appearance	Amber
Specific Gravity @ 15.6°C	0.890
Kinematic Viscosity @ 100°C (cSt)	15.71
Kinematic Viscosity @ 40°C (cSt)	156.07
Viscosity Index	103
Flash Point COC (°C)	225



TECHNICAL DATA

Pour Point (°C)	-27
-----------------	-----

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.