



TECHNICAL DATA

AUTO-TRANS D VI

Fully synthetic automatic transmission fluid

Product code: FPATFS

Product Description:

AUTO-TRANS D VI is a premium quality, fully synthetic automatic transmission fluid and is formulated primarily for applications requiring GM's Dexron VI specification.

AUTO-TRANS D VI features many advantages over more traditional automatic transmission fluids such as improved shear stability, excellent wear control and extended fluid life.

Benefits:

- Extended fluid life
- Fuel economy benefits
- Improved low temperature performance
- Backwards compatible to previous GM Dexron specifications
- Improved frictional properties
- Outstanding wear protection
- High film strength
- Low foaming

Typical Test Data:

Appearance	Red fluid
Density @ 15.6 °C	0.845
Kinematic Viscosity @ 100°C (cSt)	6.00
Brookfield Viscosity @ -40°C (cP)	12,030
Flash Point PMCC (°C)	190
Pour Point (°C)	-53

Applications:



TECHNICAL DATA

AUTO-TRANS D VI is recommended for step type automatic transmissions and power steering units in cars, vans, trucks, buses and agricultural and industrial machines where the following specifications are required.

Product Specification:

GM	Dexron VI Dexron IIIH, IIIG, IID, TASA
JASO	1A
Allison	C-4
Caterpillar	TO-2
Mercedes-Benz	236.5
Voith	55.6335 (formerly G607)
Volvo	97340
ZF	TE-ML 09

In addition, AUTO-TRANS D VI is recommended for service fill in the following applications or where the following OEM genuine oils were originally required:

AISIN WARNER JWS 3309, JWS 3324, T IV, AW-1	FIAT (ALL VEHICLES), TYPO T IV	SAAB T IV (JWS 3309)
AS 68 RC (T IV)	HONDA / ACURA Z-1, PREMIUM	SATURN T IV (JWS 3309)
AUDI 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)	HYUNDAI / KIA SP II, SP III, SP IV & HYUNDAI SPH-IV	SCION (ALL VEHICLES)
AUDI 5 HP LT 71141 (AUDI G-052-162-A1 / A2)	NISSAN / INFINITY MATIC D, MATIC J, MATIC K, MATIC S	SHELL M 115
AUDI 5 HP (ZF 5 HP 30)	ISUZU BESCO ATF II, ATF III	SUBARU ATF, ATF HP
AUDI G-055-025-A2 (JWS 3309)	JAGUAR ATF 3403 M115, LT 71141, JLM 20238	SUZUKI ATF 3309
BMW ETL-7045, 7045E	JWS 3309 (T IV)	TEXACO ETL-7045E
BMW LA2634	JWS 3324 (WS)	TEXACO ETL-8072B
BMW 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)	MAZDA ATF M III	TOYOTA TYPE T-III, T-IV (JWS 3309)
BMW 5 HP (ZF 5 HP 30)	MERCEDES BENZ ZF HP20, 236.1, 236.5, 236.6, 236.7, 236.8, 236.9	TOYOTA WS (JWS 3324)
BMW ETL-8072B	MITSUBISHI DIAMOND SP II, SP III, SP IV	VOLVO T IV (JWS 3309)



TECHNICAL DATA

BMW MINI JWS 3309	NAG 1	VW 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)
CHRYSLER/DODGE MOPAR AS 68 RC (T IV)	OPEL (All Vehicles)	VW 5 HP LT 71141 (VW G-052-162-A1 / A2)
DAEWOO LT 71141	PEUGEOT ZF 4 HP20	VW 5 HP (ZF 5 HP 30)
ESSO LT 71141	PORSCHE ATF 3403-M115, LT 71141, T IV (JWS 3309)	VW G-055-025-A2 (JWS 3309)
FORD WSS-M2C938-A		

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.