

TECHNICAL DATA

AUTO-TRANS D III

Semi synthetic automatic transmission fluid

Product code: FPATFT

Product Description:

AUTO-TRANS D III is a multi-purpose automatic transmission fluid for commercial and passenger car gearboxes meeting a very wide range of specifications. The automatic transmission is one of the most complicated mechanisms in modern automotive engineering and consequently requires complex fluids for efficient operation.

AUTO-TRANS D III is manufactured from premium synthetic base stocks and high quality solvent refined base oils with specially selected additives and friction modifiers to produce a lubricant with outstanding durability. It demonstrates excellent frictional stability and offers extended fluid life even when under the most severe conditions.

Benefits:

- Long oil life
- Improves clutch durability
- Can be used as a power steering fluid
- Excellent protection against wear
- Low foaming tendencies
- Compatible with all elastomers and other sealing materials
- High thermal stability

Applications:

AUTO-TRANS D III is recommended for automatic transmissions and power steering units in cars, vans, trucks, buses, agricultural and industrial machines where the following specifications are required.

Product Specification:

Dexron IIIH, Dexron IIIG	MAN 339F, 339 V1 & Z1		339F, 339 V1 & Z1
--------------------------	-----------------------	--	-------------------



TECHNICAL DATA

	Dexron IID, TASA
Ford	Mercon
Allison	C-4, TES-389
Mercedes-	236.10, 236.9, 236.8, 236.7,
Benz	236.6, 236.5, 236.1
Caterpillar	TO-2

	339 V2 & Z2	
Voith	55.6335 (G607)	
Volvo	97341, 97340	
ZF	TE-ML 02F, 03D, 04D, 09,	
	11A,	
	11B, 14A, 14B, 16L, 17C	

Typical Test Data:

Appearance	Red
Density @ 15.6 ° C	0.882
Kinematic Viscosity @ 100°C	7.91
(cSt)	
Flash Point COC (°C)	205
Pour Point (°C)	-53

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.