

TECHNICAL DATA

FE 0W-20 FS

Fully synthetic, fuel efficient engine oil

Product code: FPE

Product Description:

FE 0W-20 FS is formulated to meet the extraordinary demands of high engine protection at a fuel-efficient low viscosity. It is produced using the highest quality synthetic base stocks together with state of the art additive chemistry. FE 0W-20 FS provides significant fuel saving benefits, exhibits outstanding thermal and oxidative stability and excellent protection against corrosion and black sludge.

Benefits:

- Provides significant reductions in fuel consumption
- Superior oxidative stability
- Excellent low temperature fluidity
- High thermal stability
- Outstanding wear protection
- High level of shear stability

Applications:

FE 0W-20 FS is strongly recommended for many of the latest petrol engines in Honda, Toyota, Mazda and Suzuki vehicles. It can also be used where an SAE 0W-20 meeting the following API or ILSAC specifications is called for.

Product Specification:

API	SN, SN-RC
ILSAC	GF-5

Typical Test Data:

Kinematic Viscosity @ 100°C (cSt)	8.1
Kinematic Viscosity @ 40°C	42.2



TECHNICAL DATA

(cSt)	
Viscosity Index	170
Flash Point (COC, °C)	225
TBN (mg KOH/g)	7.5
Sulphated Ash (% wt)	0.8
Pour Point (°C)	-43

Health and Safety:

Please refer to the safety data sheet, a copy of which is freely available to all our customers.