



TECHNICAL DATA

MG 15W-40

Mineral oil based engine oil
Product code: FPMF

Product Description:

MG 15W-40 is a multigrade engine oil manufactured from carefully selected base oils and the very latest additive technology. Superior dispersant additives help maintain engine cleanliness in the latest petrol engines and the latest detergent additives help reduce unwanted deposits in turbochargers and on pistons.

Benefits:

- Excellent high temperature stability
- Blended with the latest additive technology
- Excellent sludge control for stop-go city motoring
- Provides ultimate engine protection for all driving conditions

Applications:

MG 15W-40 is suitable for normally aspirated and turbocharged highly stressed petrol engines and diesel engines in the passenger cars and heavy commercials, vans, plant, buses and industrial equipment.

Product Specification:

API	SL/CH-4, CF
ACEA	A3/B3, A3/B4, E2
VW	505.00
MB	228.1, 229.1
Mack	EO-L
MAN	271
MTU	Type 1
Volvo	VDS

Typical Test Data:



TECHNICAL DATA

Specific Gravity @ 15.6°C	0.886
Kinematic Viscosity @ 100°C (cSt)	14.25
Kinematic Viscosity @ 40°C (cSt)	104.9
Viscosity Index	139
Flash Point COC (°C)	215
Pour Point (°C)	-30
TBN (mg KOH / g)	10.2

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.