



TECHNICAL DATA

Classic 20W-50

Mineral oil based engine oil

Product code: FPMOT

Product Description:

Classic 20W-50 is a high viscosity multigrade engine oil. The recommendation of a higher viscosity multigrade engine oil benefits many older engines in terms of oil consumption and emission performance. Classic 20W-50 is manufactured from selected base oils and carefully balanced additives to produce a standard quality petrol and diesel engine oil. It offers excellent high temperature stability and stay in grade performance.

Benefits:

- Moderate passenger car performance
- Cost effective
- Higher operating and higher temperature performance
- High zinc additive content

Applications:

Classic 20W-50 is suitable for normally aspirated diesel engines and petrol engines in passenger cars and vans. An ideal lubricant for the older engine. It is miscible with all synthetic and mineral based engine oils.

Product Specification:

API	CC/SE
CCMC	D1
Military Spec	Mil-L-2104B Mil-L-46152B

Typical Test Data:



TECHNICAL DATA

Specific Gravity @ 15.6°C	0.887
Kinematic Viscosity @ 100°C (cSt)	17.89
Kinematic Viscosity @ 40°C (cSt)	147.97
Viscosity Index	134
Flash Point COC (°C)	213
Pour Point (°C)	-28
TBN (mg KOH / g)	3.59

Health & Safety:

Please refer to the relevant safety data sheet, a copy of which is freely available to all of our customers.