



TECHNICAL DATA

C5 0W-20 PC LS

Fully Synthetic Low SAPS Engine Oil

Product code: FPPC

Product Description:

C5 0W-20 PC LS is an advanced synthetic engine oil, formulated and used for Stellantis (ex-PSA Group) factory fill and after sales. This pollution-control synthetic engine oil provides engines with the best possible protection against wear and clogging. The post-treatment systems, sensitive to the lubricants used and expensive to maintain, are also protected over the long-term thanks to the "Low SAPS" formulation (low content of sulphated ash, phosphorus and sulphur contents). Using this engine oil can help generate fuel savings without the need to change driving style. It is also suitable for the most demanding driving conditions (door-to-door, sports driving, repeated start-ups, city and motorway driving, etc.).

Benefits:

- Reduced environmental impact: Fuel savings of 3.3% as measured by the official ACEA M111 FE test. It guarantees compliance with all the performance levels claimed by PEUGEOT, CITROËN and DS in relation to environmental standards.
- Protection for pollution-control systems: This engine oil optimises the way in which three-way catalytic converters and particulate filters operate, preventing them from getting clogged up with soot or sludge deposits. This reduces particulate emissions, NOx, HC and CO in particular.
- Engine protection and cleanliness: This oil offers the best possible protection in its category against wear and clogging as soon as the engine is started up.
- Easier cold starts: The 0W-20 grade, together with special additives, makes cold engine starts easier, even at very low temperatures (validation tests carried out down to -40°C).
- Oil change intervals: C5 0W-20 PC LS retains all of its properties, in accordance with the service plans recommended by PEUGEOT, CITROËN and DS.

Applications:

C5 0W-20 PC LS is particularly well-suited for use with recent engines of Stellantis/PSA (DV5R and EB2DT), and particularly ones equipped with BLUE HDi, PureTech using Stop & Start technologies, and hybrid engines which require new-generation engine oils.



TECHNICAL DATA

Product Specification:

ACEA	C5
API	SN Plus
PSA	B71 2010
Opel/Vauxhall	OV 040 1547-A20

- Meets the requirements of Fiat 9.55535-DM1

Typical Test Data:

Appearance	Clear & Bright
Density @ 15°C	0.845
Kinematic Viscosity @ 100°C (cSt)	8.20
Kinematic Viscosity @ 40°C (cSt)	43.9
Viscosity Index	166
Pour Point (°C)	-42
Flash Point, Open (°C)	233

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.