



TECHNICAL DATA

C3 5W-30 PRO LSVW

Fully Synthetic Low SAPS Engine Oil

Product code: FPPV

Product Description:

C3 5W-30 PRO LSVW is a fully synthetic multigrade engine oil formulated from hydrocracked synthetic base stocks, an advanced detergent-dispersant additive package, and shear stable polymers.

C3 5W-30 PRO LSVW is a low SAPS (sulphated ash, phosphorus and sulphur) product which is compatible with low emission after-treatment systems and is suitable for use in a wide range of modern passenger car and light duty commercial vehicle engines.

Benefits:

- Diesel particulate filter compatible
- Improves fuel economy
- Long service life
- Very high thermal stability
- Recommended for many VW/Audi models

Applications:

C3 5W-30 PRO LSVW is recommended for use in a wide variety of passenger cars and vans with petrol and diesel engines, including those that require a low SAPS oil.

Product Specification:

ACEA	C3
API	SN

Recommended by FAI in the following applications:

VW	504.00/507.00
Mercedes-Benz	229.51

BMW	Longlife-04
Porsche	C30



TECHNICAL DATA

Typical Test Data:

Density @ 15°C	0.857
Kinematic Viscosity @ 100°C (cSt)	12.21
Kinematic Viscosity @ 40°C (cSt)	73.0
Viscosity Index	166
Flash Point, COC (°C)	230
TBN (mg KOH/g)	7.3

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.