

TECHNICAL DATA SHEET

C2 0W-30 BM LS

Fully synthetic low SAPS engine oil

Product code: FPOB

Product Description:

C2 0W-30 BM LS is a fully synthetic low ash automotive engine oil which provides fuel economy benefits without compromising engine protection. It is based on high thermal stability base oil and uses a complex combination of high performance additives which provide excellent engine cleanliness, anti-wear protection and outstanding oxidation resistance. C2 0W-30 BM LS combines a relatively high total base number for long drain performance with low ash particulate-friendly properties.

Benefits:

- Fuel saving technology
- Compatibility with after treatment systems
- Fully synthetic, long drain formulation
- Very high standards of engine cleanliness
- Superior cold starting performance

Applications:

C2 0W-30 BM LS is recommended for use in the latest BMW petrol and diesel engine vehicles including those with petrol particulate filters. It is an ideal choice for BMW diesel engines from model year 2014 onwards with no more than one turbocharger. In particular, it should be used where the BMW Longlife-12 FE specification is required.

Product Specification:

| ACEA | C2, A5/B5 |
|---------------|----------------|
| ILSAC | GF-6 |
| Mercedes Benz | 229.61, 227.61 |

| API | SP, SP-RC |
|------|----------------|
| BMW | Longlife-12 FE |
| Ford | WSS-M2C950-A |

Recommended where Fiat 9.55535-DS1, Fiat 9.55535-GS1 or Iveco 18-1811 SC1 LV are required

Typical Test Data:



TECHNICAL DATA SHEET

| Specific Gravity @ 15.6°C | 0.842 |
|-----------------------------------|-------|
| Kinematic Viscosity @ 100°C (cSt) | 9.91 |
| Kinematic Viscosity @ 40°C (cSt) | 53.82 |
| Viscosity Index | 174 |
| Flash Point COC (°C) | 226 |
| Pour Point (°C) | -51 |
| TBN (mg KOH / g) | 8.1 |

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.